

**Torque screwdriver set TorqueVario®-S electric
0,8-5,0 Nm PlusMinus/Pozidriv variably adjustable
torque limit 5-pcs. (38074)**



Wiha Werkzeuge GmbH
Obertalstraße 3-7
78136 Schonach
E-Mail: info.de@wiha.com
Tel.: +49 (0)7722 959-0



Order no.: 38074

Article number: 38074

EAN: 4010995380748

Customs tariff number: 82054000

Increases your efficiency: The correct torque protects material from damage and means no follow-up work.

Lowers your costs: The correct torque protects you from warranty claims.

Offers you full protection: Each tool individually tested at 10,000 V AC and approved for 1,000 V AC.

Increases your safety: Wiha slimBits ensure good, protected access to deep-set screws.

Protects your health: With the patented SoftFinish® handle design, ensuring work is kind to hands and muscles. Recommended by doctors and therapists at German Campaign for Healthier Backs.

Meets your requirements: Variably adjustable torque covers a wide range of applications.

Product dimensions: 190 x 50 x 50 mm (LxWxD)

Application: For controlled fastening on live parts up to 1 000 V AC.

Standards: Manufactured acc. to IEC 60900.

Variably adjustable torque from 0.8 - 5.0 Nm

Acoustic and physically perceptible triggering signal protects against damage to materials and rework

slimBits allow access to low-lying screws thanks to inserted insulation

Safe operation up to 1,000 V AC

Expandable and compatible with EVF products

With handle, 2 slimBits, adapter, and adjusting tool

The fully certified TorqueVario®-S VDE torque system offers controlled screw tightening coupled with safety for electronic applications. The tool set contains an ergonomically shaped torque screwdriver handle with integrated numeric scale, 2 slimBits, a bit holder, as well as the adjusting tool. All components are arranged practically and clearly in a high-grade, hard-wearing box, incl. the manufacturer's inspection process report. The VDE torque screwdriver covers a wide variety of applications with a variably adjustable torque range between 0.8 and 5.0 Nm. A clearly audible, physically perceptible signal emitted when the torque is produced guarantees process-safe torque mechanics, protecting against damage to materials and eliminating the need for retouching. With a release accuracy of +/-6%, the torque tool complies with the requirements of DIN EN ISO 6789. The insulated ClicFix bit holder guarantees a secure hold for 75 mm long slimBits thanks to mechanical blade locking. Both the torque screwdriver and the

slimBits undergo routine testing as per the international IEC 60900 standard, allowing users to work safely on live parts up to 1,000 V AC.

DIN EN ISO 6789.

Content:

- 1x Torque screwdriver TorqueVario®-S electric variably adjustable torque limit 0.8 - 5 (26626)
- 1x Setting tool for torque screwdriver with long handle 90 mm (26864)
- 1x Adapter TorqueVario-S electric for slimBits 6.0 mm (35870)
- 1x slimBit electric bit PlusMinus/Pozidriv SL/PZ1 x 75 mm (34589)
- 1x slimBit electric bit PlusMinus/Pozidriv SL/PZ2 x 75 mm (34590)

Customs tariff number	82054000
-----------------------	----------

Self service - packing	No
------------------------	----

Tool for electrics	Yes
--------------------	-----

Country of origin (ISO 3166-1 Alpha 3)	DEU
--	-----
